



# 2.4

## QUICK DISCONNECT TERMINAL BLOCKS

for solid wires · MINI series



	PC2252-CL	PC2253-CL
	<b>2x2.5<sup>□</sup></b>	<b>3x2.5<sup>□</sup></b>
Colour   Cat. number		
Transparent ○	89 021 000	89 022 000
Standard		
Certificate/Declaration	CE	CE
Rated cross-section		
Solid wire	0.5 ... 2.5 mm <sup>2</sup>	0.5 ... 2.5 mm <sup>2</sup>
Number of tracks	2	3
Current data		
Rated voltage	450 V	450 V
Rated current	24 A	24 A
Operating temperature	-30°C ... +85°C	-30°C ... +85°C
External dimensions		
A / B / C	10.6 mm / 16 mm / 7.3 mm	15 mm / 16 mm / 7.3 mm
Stripped wire length	11 mm	11 mm
Weight	1.8 g	2.3 g
Collective packaging	100 pcs	100 pcs
Material	polycarbonate + stainless steel + tinned copper	polycarbonate + stainless steel + tinned copper



	PC2254-CL	PC2255-CL	PC2258-CL
	<b>4x2.5<sup>□</sup></b>	<b>5x2.5<sup>□</sup></b>	<b>8x2.5<sup>□</sup></b>
Colour   Cat. number			
Transparent ○	89 023 000	89 024 000	89 005 000
Standard			
Certificate/Declaration	CE	CE	CE
Rated cross-section			
Solid wire	0.5 ... 2.5 mm <sup>2</sup>	0.5 ... 2.5 mm <sup>2</sup>	0.5 ... 2.5 mm <sup>2</sup>
Number of tracks	4	5	8
Current data			
Rated voltage	450 V	450 V	450 V
Rated current	24 A	24 A	24 A
Operating temperature	-30°C ... +85°C	-30°C ... +85°C	-30°C ... +85°C
External dimensions			
A / B / C	19.4 mm / 16 mm / 7.3 mm	23.8 mm / 16 mm / 7.3 mm	17.9 mm / 17.6 mm / 14.3 mm
Stripped wire length	11 mm	11 mm	11 mm
Weight	2.9 g	3.5 g	4.9 g
Collective packaging	100 pcs	100 pcs	50 pcs
Material	polycarbonate + stainless steel + tinned copper	polycarbonate + stainless steel + tinned copper	polycarbonate + stainless steel + tinned copper